

1- SERIAL NUMBER
NUMERO DE SERIE

M2020013350

2- MODEL
MODELE

30RB-160R-PI1897-

CE 0062

47- DESCRIPTION
DESCRIPTION

3- VARIANT
VARIANTE

VAR41

4- YEAR OF MANUFACTURE AND TEST DATE 29/10/2020
ANNEE DE FABRICATION ET DATE D'ES

48- HERMETICALLY SEALED EQUIPMENT
EQUIPEMENT HERMETIQUEMENT SCELLE

N

49- CONTAINS FLUORINATED GREENHOUSE GASES
CONTIENT DES GAZ FLUORES A EFFET DE SERRE

Y



25- FLUID DURING TRANSPORT
FLUIDE PENDANT LE TRANSPORT

R-32

10.14

kg

5- REFRIGERANT
REFRIGERANT

R-32

6- PED GROUP 1
PED GROUPE 1

GWP

675

50- CIRCUIT
CIRCUIT

A

/

B

/

C

7- FACTORY CHARGE
CHARGE USINE

5.07

/

5.07

/

*

kg

51- CHARGE ADDED ON SITE
CHARGE AJOUTEE SUR SITE

/

/

kg

52- TOTAL CHARGE
CHARGE TOTALE

5.07

/

5.07

/

*

kg

3.42

/

3.42

/

*

t.eq.CO2

9- INERTING MEDIUM
FLUIDE D'INERTAGE

23- NITROGEN

21- HIGH PRESSURE
HAUTE PRESSION

22- LOW PRESSURE
BASSE PRESSION

10- ALLOWABLE PRESSURE MIN/MAX
PRESSION MINI / MAXI ADMISSIBL

(PS)

(-1.0 / 47.0 bar

-1.0 / 31.1 bar)

-99.0 / 4700.0 kPa

-99.0 / 3110.0 kPa

53- ALLOWABLE TEMPERATURE MAXI
TEMPERATURE ADMISSIBLE MAXI

(TS)

70.0 / 150.0 °C

51.0 °C

54- ALLOWABLE TEMPERATURE MINI
TEMPERATURE ADMISSIBLE MIN

(TS)

-20.0 °C

-20.0 °C

12- PRESSURE SAFETY SWITCH SETTING 1/2
TARAGE PRESOSTATS DE SECURITE 1/2

47.0

/

*

bar

*

/

*

bar

55- TEST PRESSURE
PRESSION D'ESSAI

(PS)

51.7 bar

34.2 bar

13- RELIEF VALVE SETTING

PRESSION DECLenchement SOUPAPES

*

bar

*

bar

15- VOLTAGE
TENSION

400

V

+10 % -10 %

16- PHASES 3
PHASES

17- FREQUENCY ~ 50 Hz
FREQUENCE

18- MAXIMUM AMPS
I MAXIMALE

124.00

/

*

A

19- MAX POWER INPUT
PUISSANCE ABSORBE

73.00

/

*

kW

20- NET WEIGHT
POIDS NET

931

kg

+5 % -5 %



United Technologies

Route de Thil 01120 Montluel



PLS TriCkt V4r2